



▶ PRODUCT SUMMARY

The Shuttle All-in-One PC Barebone X50V4 is the latest addition to the X50 Series and is powered by Intel's Celeron 2957U processor. The latest 22nm Haswell architecture helps improve on power consumption and computing power. Thanks to its passive cooling, the system is virtually noiseless, maintenance-free and is approved for 24/7 nonstop operation. Particularly suitable for vertical applications is the arrangement of connectors at the bottom and the IP54 compliant front panel which is dust-protected and protected from splashing of water.

▶ KEY FEATURES

- All applications at your fingertips
- Light Stylish AIO (All-In-One)
- Intel® Celeron™ dual-core processors
- HDMI and VGA Ports
- Built-In Webcam and Microphone
- Fanless Design
- 4-Point Touch Screen Calibration
- Optional serial and parallel legacy ports
- 24/7 non-stop operation

▶ PRODUCT AVAILABILITY: DECEMBER 2014

FORM FACTOR	Shuttle AIO Form Factor	
DIMENSIONS	15.4 x 12.9 x 1.7(inches)	
PROCESSOR	Intel Celeron 2957U dual core CPU	
OS SUPPORT	Support Windows 7 32/64 bit O.S Support Windows 8 32/64 bit O.S Support Windows 7 & 8 32/64 bit Embedded O.S Support Ubuntu, Fedora Linux O.S	
MEMORY	1 x DDR3L SO-DIMM Memory Slot (support up to 8GB)	
AUDIO	Realtek ALC269 HD Audio 2W x 2 Internal Stereo speaker	
ETHERNET	Realtek 8111G IEEE 802.3u 100Base-T specification compliant 10MB/s,100MB/s, 1000MB/s Support wake ON LAN (WOL) feature	
VGA	Intel HD graphic engine	
STORAGE INTERFACE	2.5" SATA II device bay x 1	
LCD PANEL	15.6" 16:9 Wide Panel, 1366 x 768 pixels	
TOUCH SCREEN	Single Touch	
WEB CAM	2.0M FHD, HD Pixel	
MIC	Electret Condenser Microphone	
LEFT SIDE	Power-on Button Stylus Pen	2 x USB 2.0 Clear CMOS Reset Button
BACK PANEL	1 x VGA 1 x Line out 1 x MIC in 1 x HDMI 2 x USB 3.0 1 x RJ45 LAN	2 x USB 2.0 DC in Kensington security slot COM3, COM4 of RJ45 (Optional) RJ11 DIO Port for Cash Drawer (Optional)
WIRELESS LAN	Built in 802.11b/g/n WLAN module	
NET WEIGHT	7.9 lb (3.6 kg)	
POWER	65W Power Adaptor Input 100 – 240V AC Output 19V 3.42A DC	
OPERATING TEMPERATURE	0~40 °C (Humidity: 10-90%)	

For more information on all computer products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2014 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.