

XH110V

xpc SLIM

FORM FACTOR	Mini-ITX MB	3.5 L chassis
CHIPSET	Intel® H110 Express chipset	
PROCESSOR	Support Intel® Skylake Core® i3/i5/i7, Pentium®, Celeron® CPU max. TDP 65W	
MEMORY	2 x 204 pin DDR3L SODIMM slots, 16GB per DIMM (Max 32GB) Dual Channel DDR3L 1600 Mhz	
VGA	HDMI + Display port dual display	
AUDIO	Realtek ALC662 5.1 channel High Definition Audio	
ETHERNET	Intel i211+i219LM Dual Lan 100Mb/s and 1Gb/s operation	Support Wake-On-LAN function Support Teaming function
STORAGE INTERFACE	SATA 6.0Gb/s interface	
ONBOARD CONNECTORS	3) SATA connectors (2) 1x5 pin USB 2.0 header (1) ATX main power connector	(1) ATX 12V power connector (2) set 4pin fan connectors
FRONT PANEL	(2) USB 2.0 ports (2) USB 3.0 ports (1) Microphone-In (1) Earphone-Out	Power-On button Power LED HDD LED
BACK PANEL	(2) RJ45 Gigabit LAN port (1) Display port (1) HDMI (2) USB 2.0 ports (2) USB 3.0 ports (1) RS232 (1) RS232/RS422/RS485 (1) Line in port	(1) Line out port (1) MIC in port (1) Clear CMOS button (1) DC in (1) PS/2 port (1) Kensington lock (2) Wireless Antenna fixture
DRIVE BAYS	(1) 2.5" HDD / SSD bay (1) Slim ODD bay	User can install either 1 Slim ODD or (1) 2.5" HDD/SSD
DIMENSIONS	XH110V: 240(L) x 200(W) x 72(H) mm	
POWER	90W Power Adapter	Input: 100- 240V AC Output: 19V 4.47A DC
EXPANSION SLOT	(1) M.2 2280 Type M key socket	(1) M.2 2230 Type A,E Key socket
OS SUPPORT	Windows 7 / Windows 8.1 / Windows 10 / Linux	



XH110V



XH110V Front (Open Panels)



XH110V Back

ACCESSORIES

- XPC Multi-language Quick User Guide
- XPC DVD Driver
- 1* Power cord
- 1* SATA cable (pre-install for HDD)
- 1* SATA cable (pre-install for ODD)
- 1* 4 pin to SATA power cable
- Screws

REMARK* PCH4 3.5" HDD rack accessory can support XH110V.

For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.

XH110V vs XH81V



PROCESSOR SUPPORT	1151 Skylake	1150 Haswell / Haswell Refresh
CHIPSET	H110	H81
VGA	Base on Different CPU Max. HD530	Base on Different CPU Max. HD4600
VGA I/O	1x HDMI 1x DisplayPort	1x HDMI 2x DisplayPort
SATA	1x SATA 6G 1x eSATA	1x SATA 3G 2x SATA 6G
USB	4x USB 2.0 4x USB 3.0	6x USB 2.0 2x USB 3.0
EXPANSION SLOT	1x M.2 2280 Type M 1x M.2 2230 Type A,E	1x Mini-PCIe (Full size) 1x Mini-PCIe (Half size)
MEMORY	DDR3L SODIMM x 2 up to 32GB total (16GB x 2)	DDR3 SODIMM x 2 up to 16 GB total (8GB x 2)

For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.