

NS02A/NS02E

xpc NANO

FORM FACTOR	Shuttle 0.57L	
PROCESSOR	Rockchip RK3368 Octal Core Cortex-A53, 64 bit SoC, 1.5Ghz max.	
MEMORY	2GB Onboard	
VIDEO GRAPHICS	GC6110 GPU (NS02A)/ PowerVR SGX6110 GPU up to 600 Mhz OpenGL ES 3.1 / OpenCL 1.2 / DX 9.3	
VIDEO OUTPUT	HDMI	
AUDIO	Realtek ALC5640-VB	
ETHERNET	RTL8211F-CG 10/100/1000 Mb/s RTL8723BS 802.11 b/g/n 1T1R with Bluetooth 4.0 Miracast support	
STORAGE INTERFACE	eMMC 16GB onboard Supports 2.5" 7mm SATA interface HDD	
FRONT PANEL	(1) Power Button (1) Power LED (1) HDD LED	(2) USB 2.0 (1) SD Card Reader
BACK PANEL	(1) HDMI port (1) RJ45 Gigabit LAN port (1) USB 2.0 (1) DC-in jack	(1) Kensington Lock (1) Line-out 3.5mm jack
DIMENSIONS	5.55(L) x 5.55(W) x 1.14(H) inches	
POE (NS02E only)	Power over Ethernet (PoE) Powered device (PD) with 12V input, 802.3at compliant	
POWER (NS02A only)	Input 100 - 240V AC Output 12V 2A DC	24W power adapter
ACCESSORIES	Quick guide VESA mount (optional) Vertical stand (optional)	Rubber Mats HDD rack and cable (optional) 12V/24W external adapter (optional)
EXPANSION SLOT	2.5" 7mm HDD (supports one SATA HDD or SSD)	
OS SUPPORT	Android 5.1 Preinstall	
CERTIFICATIONS	CE, FCC, BSMI, RCM, CCC, R&TTE, CB, ETL, RoHS, EuP Lot 6	



For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.