

NC03U/U3/U5/U7

xpc NANO

FORM FACTOR	Shuttle 0.85L	
PROCESSOR	Intel Kabylake-U Celeron 3865U 15W Processor i3-7100U (NC03U3), i5-7200U (NC03U5), i7-7500U (NC03U7)	
MEMORY	2 x 260 pin DDR4 SODIMM slots, 16 GB per DIMM (Max. 32GB) Dual Channel DDR4 2133 Mhz	
VIDEO GRAPHICS	Intel® HD Graphics	
VIDEO OUTPUT	HDMI + DisplayPort	
AUDIO	Realtek ALC662 HD audio	
ETHERNET	Intel i211, supports 10/100/1000 Mb/s	
WI-FI	Realtek RTL8188EE 802.11 b/g/n Wireless LAN	
STORAGE INTERFACE	Supports SATA 6.0 GB/s bandwidth	
FRONT PANEL	(1) Power Button (1) Power LED (1) HDD LED	(1) USB 3.0 Type A (1) USB 3.0 Type C (1) SD Card Reader
BACK PANEL	(1) HDMI port (1) DisplayPort (2) USB 2.0 (1) RJ45	(1) DC-in (1) Headphone + MIC-in (1) RS232 (1) Kensington Lock
DRIVE BAYS	(1) 2.5" 15mm HDD/SSD	
DIMENSIONS	5.59(L) x 5.59(W) x 1.65(H) inches	
POWER	Input 100 - 240V AC (50/60Hz), auto voltage adjustment 65W (19V/3.42A), 2 pin	
ACCESSORIES	Quick guide VESA mount Vertical stand (optional)	Driver DVD Power adapter Power cord
EXPANSION SLOT	(1) M.2 2230 A,E key (built in Wi-Fi) (1) M.2 2280 M key	(1) 2.5" 15mm SATA
OS SUPPORT	Windows 10, Linux	



For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2017 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.