

X50V6

xpc AIO

PROCESSOR	Intel® Kabylake-U Celeron® 3865U 15W CPU i3-7100U (Optional)	
MEMORY	2 x DDR4 2133 Mhz SODIMM, 16GB per DIMM (Max. 32GB)	
VIDEO GRAPHICS	Intel® HD Graphics	
VIDEO OUTPUT	HDMI	
AUDIO	Realtek ALC269 Two Channel High, 2W x 2 Stereo speaker	
ETHERNET	Intel i219LM 10/100/1000 MB/s operation	Supports Wake-On-LAN function
WI-FI	Realtek RTL8188EE	
STORAGE INTERFACE	(1) 2.5" SATA3 device bay	
LCD PANEL	15.6" 16:9 wide panel 1366 x 768 pixels	
TOUCH SCREEN	Single Touch	
WEBCAM	720P / 2MFHD	
MIC	Electret Condenser Microphone	
FRONT PANEL (LEFT)	(1) Power-on button (1) Stylus pen (2) USB 2.0 port	(1) SD Card Reader (1) Clear CMOS
BACK PANEL	(2) USB 2.0 ports (2) USB 3.0 ports (1) HDMI (1) LAN	(1) MIC-in (1) DC-in (1) Kensington lock (1) Headphone jack
DIMENSIONS	15.4(L) x 12.9(W) x 1.67(H) in	
POWER	Input: 100 – 240V AC Output: 19V/3.42A DC or 12V/5.42A	65W 19V adapter bundled
EXPANSION SLOT	(1) M.2 2280 Type B,M key socket	(1) M.2 2230 Type A,E Key socket
SOFTWARE	Shuttle Control AP	



For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.