

# NS02A/NS02E

**xpc NANO**

<b>FORM FACTOR</b>	Shuttle 0.57L	
<b>PROCESSOR</b>	Rockchip RK3368 Octa Core SoC, 1.5Ghz max.	
<b>MEMORY</b>	2 GB Onboard	
<b>VIDEO GRAPHICS</b>	GC6110 GPU (NS02A)	
<b>VIDEO OUTPUT</b>	HDMI	
<b>AUDIO</b>	Realtek ALC5640-VB	
<b>ETHERNET</b>	RTL8211F-CG 10/100/1000 Mb/s RTL8723BS 802.11 b/g/n 1T1R with Bluetooth 4.0 Miracast support	
<b>STORAGE</b>	eMMC 16GB onboard	
<b>FRONT PANEL</b>	(1) Power Button (1) Power LED (1) HDD LED	(2) USB 2.0 (1) SD Card Reader
<b>BACK PANEL</b>	(1) HDMI port (1) RJ45 Gigabit LAN port (1) USB 2.0 (1) DC-in jack	(1) Kensington Lock (1) Line-out 3.5mm jack
<b>DIMENSIONS</b>	5.55(L) x 5.55(W) x 1.14(H) inches	
<b>POE</b> (NS02E only)	Power over Ethernet (PoE) Powered device (PD) with 12V input, 802.3at compliant	
<b>POWER</b> (NS02A only)	Input 100 - 240V AC Output 12V 2A DC	24W power adapter
<b>ACCESSORIES</b>	Quick guide VESA mount (optional) Vertical stand (optional)	Rubber Mats HDD rack and cable (optional) 12V/24W external adapter (optional)
<b>EXPANSION SLOT</b>	2.5" 7mm HDD support	
<b>OS SUPPORT</b>	Android 5.1 Preinstall	
<b>CERTIFICATIONS</b>	CE, FCC, BSMI, RCM, CCC, R&TTE, CB, ETL, RoHS, EuP Lot 6	



For more information on all products, please contact us at [sales@us.shuttle.com](mailto:sales@us.shuttle.com) or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.  
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.