

# DH02U/U3/U5/U7

**xpc SLIM**

<b>PROCESSOR</b>	Intel® Kabylake-U Celeron 3865U 15W CPU i3-7100U, i5-7200U, i7-7500U (optional)	
<b>MEMORY</b>	2 x 260 pin DDR4L SODIMM slots, 16GB per DIMM (Max 32GB), DDR4 2133 MHz, dual channel	
<b>VIDEO GRAPHICS</b>	NVIDIA GeForce GTX 1050 (MXM card), 4GB GDDR5	
<b>VIDEO OUTPUT</b>	HDMI 2.0, Supports four independent UHD displays 4K/2K playback (dual channel memory recommended)	
<b>AUDIO</b>	Realtek ALC662 HD audio	
<b>ETHERNET</b>	Intel Chip i211 100Mb/s, 1GB/s operation	Supports Wake-On-LAN function
<b>STORAGE</b>	SATA 6.0GB/s interface	
<b>ONBOARD CONNECTORS</b>	(1) SATA power w/ connector (2) 4 pin fan connectors	(1) RS232 (1) Auto power on header
<b>FRONT PANEL</b>	(1) Power button (1) Power LED (1) HDD LED (2) USB 3.0 ports	(2) USB 2.0 ports (1) MIC-in (1) External headphone jack 1/8" (1) SD card reader
<b>BACK PANEL</b>	(4) HDMI ports (2) USB 3.0 ports (1) RJ45 Gigabit LAN port (1) Kensington lock	(1) RS232* (1) Clear CMOS header (2) Wireless antenna fixture (1) DC-in
<b>DRIVE BAYS</b>	(1) 2.5" HDD/SSD drive supported	
<b>DIMENSIONS</b>	7.5(L) x 6.5(W) x 1.7(H) inches	
<b>POWER</b>	Input: 100—240V AC Output: 19V 6.32A DC	120W power adapter
<b>ACCESSORIES</b>	Quick guide Driver DVD Power cord Screws	VESA mount VESA mount quick guide SATA cable 802.11ac/b/g/n WLAN module (optional)
<b>EXPANSION SLOT</b>	(1) M.2 2230 Type E key socket (1) M.2 2280 Type M key socket	(1) MxM 3.0 Type A
<b>OS SUPPORT</b>	Windows 10 64 bit, Linux	



\*RS232 ports support a max of 500mA, 0/5/12V output (please refer to voltage settings in the quick guide)