

DH02U/U3/U5/U7

xpc SLIM

PROCESSOR	Intel® Kabylake-U Celeron 3865U 15W CPU i3-7100U, i5-7200U, i7-7500U (optional)	
MEMORY	2 x 260 pin DDR4L SODIMM slots, 16GB per DIMM (Max 32GB), DDR4 2133 MHz, dual channel	
VIDEO GRAPHICS	NVIDIA GeForce GTX 1050 (MXM card), 4GB GDDR5	
VIDEO OUTPUT	HDMI 2.0, Supports four independent UHD displays 4K/2K playback (dual channel memory recommended)	
AUDIO	Realtek ALC662 HD audio	
ETHERNET	Intel Chip i211 100Mb/s, 1GB/s operation	Supports Wake-On-LAN function
STORAGE	SATA 6.0GB/s interface	
ONBOARD CONNECTORS	(1) SATA power w/ connector (2) 4 pin fan connectors	(1) RS232 (1) Auto power on header
FRONT PANEL	(1) Power button (1) Power LED (1) HDD LED (2) USB 3.0 ports	(2) USB 2.0 ports (1) MIC-in (1) External headphone jack 1/8" (1) SD card reader
BACK PANEL	(4) HDMI ports (2) USB 3.0 ports (1) RJ45 Gigabit LAN port (1) Kensington lock	(1) RS232* (1) Clear CMOS header (2) Wireless antenna fixture (1) DC-in
DRIVE BAYS	(1) 2.5" HDD/SSD drive supported	
DIMENSIONS	7.5(L) x 6.5(W) x 1.7(H) inches	
POWER	Input: 100—240V AC Output: 19V 6.32A DC	120W power adapter
ACCESSORIES	Quick guide Driver DVD Power cord Screws	VESA mount VESA mount quick guide SATA cable 802.11ac/b/g/n WLAN module (optional)
EXPANSION SLOT	(1) M.2 2230 Type E key socket (1) M.2 2280 Type M key socket	(1) MxM 3.0 Type A
OS SUPPORT	Windows 10 64 bit, Linux	



*RS232 port supports a max of 500mA, 0/5/12V output (please refer to voltage settings in the quick guide)