

# XH110G

**xpc SLIM**

<b>FORM FACTOR</b>	Shuttle 3L chassis	
<b>PROCESSOR</b>	Supports Intel® Skylake/Kabylake Core™ i3/i5/i7, Pentium®, Celeron® TDP 65W CPU, LGA 1151	
<b>CHIPSET</b>	Intel® H110 Express Chipset	
<b>MEMORY</b>	2 x DDR4 SODIMM slots, 16GB per DIMM (Max 32GB) Dual Channel DDR4 2133/2400 Mhz	
<b>VIDEO GRAPHICS</b>	Intel HD Graphics, Max HD 630 (depending on CPU)	
<b>VIDEO OUTPUT</b>	HDMI + VGA, Supports dual display	
<b>AUDIO</b>	Realtek ALC662 HD 5.1 channel audio	
<b>ETHERNET</b>	Intel i211	Supports S3,S4,S5 and Wake-On-LAN function 10/100/1000 MB/s operation
<b>STORAGE INTERFACE</b>	SATA 6 GB/s interface	(1) M.2 2242/2260/2280 Type M slot
<b>DRIVE BAYS</b>	(1) 2.5" HDD/SSD bay	
<b>ONBOARD CONNECTORS</b>	(1) SATA connector w/ power (1) 4 pin fan connector	
<b>FRONT PANEL</b>	(1) Power Button (1) Power LED (1) HDD LED (2) USB 2.0	(2) USB 3.0 (1) External microphone jack 1/8" (1) External headphone jack 1/8"
<b>BACK PANEL</b>	(1) HDMI (1) VGA (4) USB 2.0 (1) RJ45	(1) PCI-E slot (1) Clear CMOS (1) DC-in (1) Kensington Lock
<b>POWER</b>	Input: 100—240V AC Output: 19.5V/9.23A DC	180W adapter
<b>ACCESSORIES</b>	Quick Guide Driver DVD Power cord 180W adapter Screw pack	VESA bracket VESA screw pack WLN-M (optional wireless + BT card) PS01 (optional stand)
<b>DIMENSIONS</b>	9.8 x 7.9 x 3 inches (LxWxH)	
<b>EXPANSION SLOT</b>	(1) M.2 2230AE key socket	(1) PCI-E X16
<b>OS SUPPORT</b>	Windows 7 (Skylake only), Windows 10, Linux	



For more information on all products, please contact us at [sales@us.shuttle.com](mailto:sales@us.shuttle.com) or 626.820.9000

© 2017 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.  
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.