

# XH110

**xpc SLIM**

<b>FORM FACTOR</b>	Mini-ITX MB	3.5 L chassis
<b>CHIPSET</b>	Intel® H110 Express chipset	
<b>PROCESSOR</b>	Support Intel® Skylake Core® i3/i5/i7, Pentium®, Celeron® CPU max. TDP 65W	
<b>MEMORY</b>	2 x 204 pin DDR3L SODIMM slots, 16GB per DIMM (Max 32GB) Dual Channel DDR3L 1600 Mhz	
<b>VGA</b>	HDMI + Display port dual display	
<b>AUDIO</b>	Realtek ALC662 5.1 channel High Definition Audio	
<b>ETHERNET</b>	Intel i211+i219LM Dual Lan 100Mb/s and 1Gb/s operation	Supports Wake-On-LAN function Supports Teaming function
<b>STORAGE INTERFACE</b>	SATA 6.0Gb/s interface	
<b>ONBOARD CONNECTORS</b>	(3) SATA connectors (2) 1x5 pin USB 2.0 header (1) ATX main power connector	(1) ATX 12V power connector (2) set 4pin fan connectors
<b>FRONT PANEL</b>	(2) USB 2.0 ports (2) USB 3.0 ports (1) Microphone-In (1) Earphone-Out	Power-On button Power LED HDD LED
<b>BACK PANEL</b>	(2) RJ45 Gigabit LAN port (1) Display port (1) HDMI (2) USB 2.0 ports (2) USB 3.0 ports (1) RS232 (1) RS232/RS422/RS485 (1) Line in port	(1) Line out port (1) MIC in port (1) Clear CMOS button (1) DC in (1) PS/2 port (1) Kensington lock (2) Wireless Antenna fixture
<b>DRIVE BAYS</b>	(1) 2.5" HDD / SSD bay (1) Slim ODD bay	User can install either 1 Slim ODD or (1) 2.5" HDD/SSD
<b>DIMENSIONS</b>	240(L) x 200(W) x 72(H) mm	
<b>POWER</b>	90W Power Adapter Input:100- 240V AC Output: 19V 4.47A DC	
<b>EXPANSION SLOT</b>	(1) M.2 2280 Type M key socket	(1) M.2 2230 Type A,E Key socket
<b>OS SUPPORT</b>	Windows 7 / Windows 8.1 / Windows 10 / Linux	



## ACCESSORIES

- XPC Multi-language Quick User Guide
- XPC DVD Driver
- 1\* Power cord
- 1\* SATA cable (pre-installed for HDD)
- 1\* SATA cable (pre-installed for ODD)
- 1\* 4 pin to SATA power cable
- Screws

REMARK\* PCH4 3.5" HDD rack accessory can support XH110/XH110V.

For more information on all products, please contact us at [sales@us.shuttle.com](mailto:sales@us.shuttle.com) or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.  
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.

# XH110 vs XH81V



	XH110	XH81V
<b>PROCESSOR SUPPORT</b>	1151 Skylake	1150 Haswell / Haswell Refresh
<b>CHIPSET</b>	H110	H81
<b>VGA</b>	Base on Different CPU Max. HD530	Base on Different CPU Max. HD4600
<b>VGA I/O</b>	1x HDMI 1x DisplayPort	1x HDMI 2x DisplayPort
<b>SATA</b>	1x SATA 6G 1x eSATA	1x SATA 3G 2x SATA 6G
<b>USB</b>	4x USB 2.0 4x USB 3.0	6x USB 2.0 2x USB 3.0
<b>EXPANSION SLOT</b>	1x M.2 2280 Type M 1x M.2 2230 Type A,E	1x Mini-PCIe (Full size) 1x Mini-PCIe (Half size)
<b>MEMORY</b>	DDR3L SODIMM x 2 up to 32GB total (16GB x 2)	DDR3 SODIMM x 2 up to 16 GB total (8GB x 2)

For more information on all products, please contact us at [sales@us.shuttle.com](mailto:sales@us.shuttle.com) or 626.820.9000

© 2016 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.