

DH370

xpc SLIM

FORM FACTOR	Shuttle 1.3L	
PROCESSOR	Supports Intel Coffee Lake-S, Core i3/i5/i7, Pentium, Celeron CPU, max. TDP 65W	
MEMORY	2 x DDR4 SODIMM slots, 16 GB per DIMM (Max 32GB), DDR4 2400/2666 MHz	
VIDEO GRAPHICS	Intel HD graphics	
VIDEO OUTPUT	HDMI 2.0 x 1 + DisplayPort x 2, Supports triple independent display, 4K playback (Dual channel memory recommended)	
AUDIO	Realtek ALC662 HD audio	
ETHERNET	Intel Chip i211*2 Dual LAN 10Mb/s, 100Mb/s and 1GB/s operation	Supports Wake-ON-LAN function Supports Teaming function
STORAGE INTERFACE	SATA 6.0GB/s interface	
ONBOARD CONNECTORS	(1) SATA connector w/ power (1) 4pin Fan connector (1) RS232 voltage switch	(1) VGA connector (For PVG01 use) (1) Front audio header (1) Auto power on header
FRONT PANEL	(1) Power Button (1) Power LED (1) HDD LED (1) SD Card reader	(2) USB 3.1 Gen 1 ports (2) USB 3.1 Gen 2 ports (1) External microphone jack 1/8" (1) External headphone jack 1/8"
BACK PANEL	(2) RJ45 Gigabit LAN port (1) HDMI port (2) DisplayPort (2) USB 3.1 Gen 1 ports (2) USB 3.1 Gen 2 ports (2) Wireless antenna fixture	(1) RS232/RS422/RS485* (1) RS232* (1) DC in (1) External 4pin header (1) Kensington Lock
DRIVE BAYS	(1) 2.5" HDD or SSD bay	
DIMENSIONS	7.5(L) x 6.5(W) x 1.7(H) inches	
POWER	Input: 100 - 240V AC Output: 19V 4.74A DC	90W power adapter
ACCESSORIES	Quick guide Driver DVD 90W Power Adapter HDD screw pack	Power Cord Thermal grease VESA mount VESA screw pack
EXPANSION SLOT	(1) M.2 2230 Type E key socket	(1) M.2280 Type M key socket
OS SUPPORT	Windows 10 64 bit, Linux	



*RS232 ports support 0/5/12V output (please refer to voltage settings in the quick guide)

For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2018 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice.
Not responsible for any photographic or typographic errors. Photos shown may vary from actual look.